LABELS

SPECTRUM OIL COLOURS 259 Queens Road, London SW19 8NY

RABBIT SKIN GLUE

1 Kilo

Sprinkle 3½, grams (1 level desertspoon) of the granules into 100 cc/3½, fl.oz of water in a double boiler or glue pot, and heat gently, stirring continuously, until glue has dissolved.

Apply the warm liquid size to stretched canvas by brushing out thinly. Rabbit Skin Glue loses its strength with repeated heating.

Prepare only as much size as you need.

Use double strength size and two coats for rigid supports (wood panels etc.).

SPECTRUM OIL COLOURS

DATED: 02.05.95 HEALTH & SAFETY DATA SHEET

PRODUCT

RABBIT SKIN GLUE

TO INCLUDE

Rabbit Skin Glue

PRODUCT INFORMATION

Rabbit Skin Glue is supplied in small yellow pearls.

STORAGE

Store in a cool, dry place away from sources of heat and damp.

PACKAGING

Rabbit Skin Glue is packed in 250g and 1kg sizes in paper containers.

HEALTH HAZARDS

Rabbit Skin Glue is not hazardous, but handle with care to avoid dust of Rabbit Skin Glue in the air. Use a coarse paper mask when mixing.

FIRST AID TREATMENT

EYES Accidental contamination of eyes should be washed with tepid water for 10-15 minutes. If irritation persists, seek medical attention.

SKIN Remove contaminated clothing. Wash with soap & water.

INHALATION If respiratory discomfort occurs through inadequate ventilation - remove to fresh air, seek medical attention.

iNGESTION Give quantities of water only to drink. Seek medical advice.

OTHER TECHNICAL INFORMATION

FIRE This material is non-flammable. Should fire occur, fumes may be evolved. Use Carbon Dioxide or Dry Powder extinguishers. DO NOT USE WATER.

THIS PRODUCT SHOULD ONLY BE USED TO SIZE CANVAS IF AN OIL BASED PRIMER IS TO BE USED. DO NOT SIZE CANVAS IF USING ACRYLIC PRIMER.

SHOULD YOU REQUIRE ANY FURTHER INFORMATION - PLEASE CONTACT THE TECHNICAL DEPARTMENT ON 0181 542 4729 OR FAX YOUR QUERY TO 0181 545 0575