

# Double Sided Self Adhesive Tape

<b>Description</b>	This double sided tape consists of a paper tissue carrier and a modified acrylic dispersion adhesive.
<b>Product properties</b>	It has a good resistance against high temperatures, solvents and ageing. Very good adhesion, also to LSE substrates. This tape is APEO free.
<b>Specifications</b>	IMDS Registered
<b>Applications</b>	It is used for adhesion of pourous materials, such as open pour and impregnated foams, cellular polyethylene cellular rubber, EPDM, soft and hard PVC, felt, paper and wood.
<b>Storage and ageing</b>	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

## TECHNICAL DATA

<b>Carrier</b>	Tissue	
<b>Adhesive</b>	Acrylic modified	
<b>Liner</b>	Paper silicone coated brown	
<b>Plasticizer resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Thickness Total</b>	0,16 mm	6,3 Mils
<b>Tack loop</b>	● ● ● ● ● ● ● ●	
<b>Adhesion on stainless steel</b>	25 N/25mm	5,71 Lbs/inch
<b>Static shear 23°C</b>	2 kg/625mm <sup>2</sup>	4,55 Lb/inch <sup>2</sup>
<b>Static shear 70°C</b>	0,5 kg/625mm <sup>2</sup>	1,14 Lb/inch <sup>2</sup>
<b>Service temperature</b>	Between -40 and 140 °C	Between -40 and 284 °F
<b>Application temperature</b>	Minimum 15 °C	Minimum 59 °F